

KITACO NEW PRODUCTSE

SPECIAL ADVERTISEMENT FOR NEW ITEM 2009 Vol.16

3-8-13,NAGATA,HIGASHI-OSAKA OSAKA, JAPAN, 577-0015 URL http://www.kitaco.co.jp

ZOOMER (FI/CARB) 160km/h SPEEDOMETER KIT

Stepping motor type!

- For fuel injection and carburetor, 2 types available
- Electrical speedometer (Stepping motor)
- Can change suitable pulse setting for tire size
- Meter O.D.: 60mm
- LED METER LIGHT
- Conversion adapter for electrical speedometer included.

APPLICATION

- CLOCK, TRIP METER A/B and ODOMETER functions installed. Can select the function with HANDLE SWITCH
- W Use special stay and stock meter stay when installing.



* The photo is for FI model.

CYGNUS X (FI) FENDERLESS KIT

- STEEL/BLACK
- * Stock fender modification is required.



APPLICATION 28S1/2 CYGNUS X (FI)

	ZOOMER (CARBURETOR) AF58-1000001 ~ 1699999	
752-1135100	ZOOMER (FI) AF58-1700001 ~	

DURO 8 INCH TUBELESS TIRE (DM1020A 120/70-8/44L)

120 wide tire available!

- Fits with stock swing arm
- High grip type
- Sold each
- Tire brand and size: DURO DM-1020A. 120/70-8/44L
- O.D.: 372 ± 7mm
- Tread width : 118 ± 2mm
- Recommended air pressure : 100 ~ 125kpa (Weight 70kg)
- * May not fit with other maker wheel.

APPLICATION

Fits with only 8 inch 2.50 aluminum cast wheel (Tubeless type)

REAR

● FRONT

- 8 inch 3.50 aluminum rims (With tube type)
- 8 inch 2.50 aluminum cast wheel (Tubeless type)
- 8 inch 3.50 aluminum cast wheel (Tubeless type)
- ※ Does not fit with stock chain cover.
- * Does not fit with 8 inch 2.50 rims (With tube type).
- ※ Aluminum rims require tire tube.

KSR110/KLX1105-SPEED SUPER GL

Smooth acceleration by upgrading to 5-speed!

- Provides smooth acceleration by segmented gear ratio. Chosen high-strength material (machined finish) which can endure under hard driving and racing conditions.
- GEAR RATIO: 1st 3.000 2nd 1.823 3rd 1.400 4th 1.181 5th 1.086 (Stock: 1st 3.000 2nd 1.937 3rd 1.350 4th 1.086)
- Fits with stock clutch and KITACO HIGH GEARED CLUTCH OUTER
- Fits with stock kick starter gear
- Left crank case modification is required when installing.
- * Does not fit with neutral switch rotor.

APPLICATION			
KSR110	KL110A	ALL	
KI X110	KX110A	AII	



NAME	NO,
ZOOMER (FI) 160km/h SPEEDOMETER KIT	752-1135100
ZOOMER (CARB) 160km/h SPEEDOMETER KIT	752-1125100
CYGNUS X (FI) FENDERLESS KIT	691-0411000
DURO 8 INCH TUBELESS TIRE (DM1020A 120/70-8/44L)	911-1123108
KSR110/KLX110 5-SPEED SUPER CLOSED TRANSMISSION ASSY	305-4021100