THEFT PREVENTION RELATED PARTS

PROTECT KEY CYLINDER FROM DUSTS,FRICTION BY STORED INSIDE/OUTSIDE! FOR KEY MAINENANCE!

KEYHOLE MAINTENANCE!





HANDLE LOCK SERIES
ULTRA ROBOT ARM LOCK SERIES

STEP 1 CLEAN
KEY TURNING STIFF? START BY CLEANING!

STEP 2 LUBE
FLUONINE100% AMAZING LUBRICITY
FOR FINAL TOUCH AFTER CLEANING!

POWDERED LUBRICANT PREVENTS STICKY RESIDUE. CLEANER for KEYHOLES!!

ONCE SPRAY, REACH EVERY CORNER INSIDE THE KEYHOLE. HIGH DURABLE, HIGH LUBE!!

AZ cleaning agent for keyholes. Solvents power resolves oily grime, while high-pressure spray blasts away dirt dust, debris and metallic particles caused by wear. Cleans the inside of the keyhole. Formulated with boron nitride—a powdered lubricant—it leaves no sticky residue after cleaning, ensuring smooth key operation. Recommended for use with "AZ Dry Lube Spray for Key Holes".

Lubricant for keyholes from AZ. Consists of 100% fluoropolymer, prevents accumulation of impurities and helps lubricity last longer. Just give a quick spritz, the fluoropolymer will reach every corner, supports smooth key operation. If concerned about dirt or metal particles inside the keyhole, cleaning by "AZ cleaning agent for keyholes-key cleaner" can help more efficient maintenance.

株式会社エーゼット

AZ CLEANING AGENT FOR KEYHOLES KEY CLEANER 100ml



USAGE	CLEANING/LUBE FOR CYLINDER KEY, DIMPLE KEY
NOTES	●AZ ●CLEANIN AGENT FOR KEYHOLES ●FORMULATED WITH BORON NITRIDE ●CAPACITY : 100ml

CODE	PRICE	JAN CODE
880-9020000	¥880	4 960833 934001

Caution : Keep away from fire. Use in a well-ventilated area and do not store in places subject to high temperatures. Do not use on the following type of keys : Safe key、Electronic keys、Card-type Keys、High-value/expensive keys etc.

AZ LUBRICANT FOR KEYHOLES DRY LUBE SPRAY FLUONINE100% 50ml



USAGE	LUBE FOR CYLINDER KEY
NOTES	●AZ ●UBRICANT FOR KEYHOLES ●INGREDIENT : FLUOROPOLIMER、FLUORINATED OIL、FLUORORESIN ●CAPACITY : 50ml

CODE	PRICE	JAN CODE
880-9021000	¥2,200	4 960833 939006

Intructions for use : Shake well for about 10 times before use, keep the can upright while using. Insert the nozzle approximately 5 mm into the keyhole and spray for 0.5 seconds. To prevent clogging, turn the can upside down after use and spray briefly until only air comes out.